



CT48

Gasoline Walk-behind Trowels



A convincing concept of trowels: CT 48

With a trowel diameter of 1.220 millimeters the models of the CT 48 trowel range are ideal for finishing medium large areas. The trowels are optimally balanced, therefore they can be effortlessly controlled in the wide range of speeds. The transmission brake, electronic safety switch and engine speed sensor offer additional triple protection for the user. In an emergency situation the device will simply switch off and the handle will come to a stand-still after no more than a three-quarter turn. Furthermore, the unit will only start if the throttle lever is set to zero. This prevents an inadvertent rotation of the handle on start-up.

- Variable speeds: Low speeds for floating, high speeds for polishing
- Blade pitch up to 30°
- Different levels of motorization
- Performance classes from 8.3 to 13.4 hp
- Emergency shutdown

The guide handles can be chosen individually for more user comfort.



Standard guide handle with adjustable handle and fixed center pole.



Height adjustable handle with Pro-Shift® System enables continuous adjustment of the floating blade pitch as well as individual height adjustment.



Standard guide handle with adjustable handle and foldable center pole for easy transport



Different handles for ultimate ease of use:

	Handle adjustment	Pro-Shift® System	Height- adjustable	Fixed center pole	Folding center pole
Guide handle T	●			●	
Guide handle Fold-T	●				●
Guide handle ADJ-T	●		●	●	
Guide handle Fold ADJ-T	●		●		●
Guide handle ADJ-P		●	●		
Guide handle Fold ADJ-P		●	●		●

All of these handle versions are available for all models of walk-behind trowels.

Technical specifications

	CT48-8A	CT48-13A-V
L x W x H mm	2,160 x 1,220 x 1,040	2,160 x 1,220 x 1,040
Weight without handle kg	96	106
Troweling diameter mm	1,220	1,220
Pitch range °	0 - 30	0 - 30
RPM rpm	60 - 125	20 - 200
Quantity of blades	4	4
Engine / Motor	Air-cooled single-cylinder four-cycle gasoline engine	Air-cooled single-cylinder four-cycle gasoline engine
Engine / Motor manufacturer	Honda	Honda
Engine / Motor type	GX 240	GX 390
Displacement cm³	245	337
Engine performance max. (DIN ISO 3046) kW (hp)	6.2 (8.3)	10 (13.4)
at rpm rpm	3,800	3,800
Operating performance (DIN ISO 3046) kW (hp)	6.2 (8.3)	10 (13.4)
at rpm rpm	3,800	3,800
Fuel consumption l/h	2.7	2.7
Tank capacity l	6.1	6



**WACKER
NEUSON**
all it takes!

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.