# DINGO®

**WARRANTY**
5 YRS / 5,000 HRS

FIELDQUIP®
*...a cut above the rest!*

## K9D-WHL

DINGO.COM.AU | FIELDQUIP.COM.AU

# WHAT YOU GET

- The ORIGINAL DiNGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish

# PERFORMANCE

| | |
|---|---|
| Hydraulic pumps | 2 pumps |
| Pump sizes | 11 & 4cc |
| Relief pressure (AUX) | 3,200 psi (220 bar) |
| Hydraulic output | 47 L/m |
| Max travel speed | 6.4 km / h |
| Rated lift capacity | 325 kg WLL |

# DIMENSIONS

| | |
|---|---|
| Overall width | 1,040 mm |
| Overall length | 1,640 mm |
| Overall height | 1,225 mm |
| Max operating height 4 in 1 | 2,660 mm |
| Turning radius with 4 in 1 bucket | 1,300 mm |
| Angle of departure | 25° |
| Wheel base | 800 mm |
| Ground clearance | 140 mm |
| Dump height standard bucket | 1,450 mm |
| Dump height 4 in 1 bucket | 1,840 mm |
| Reach fully raised 4 in 1 bucket | 800 mm |
| Height to hinge pin | 1,960 mm |
| Machine width 4 in 1 bucket | 1,050 mm |
| Hydraulic reservoir capacity | 76 L |
| Machine mass | 976kg |
| Warranty<br>*(In accordance with Dingo warranty Terms & Conditions)* | 5 yrs / 5,000 hrs |

**1** **All wheel drive system**
Through 4 specifically designed and manufactured Parker drive motors.

**2** **High Flow Auxiliary Hydraulics**
For powering attachments through the toughest conditions.

**3** **Grease free**
For Lower Cost maintenance and Quick hitch system.

**4** **180° access**
Safer for operators - no risk of being trapped from behind and side bars.

**5** **Soft touch controls**
Minimise fatigue while providing accurate control.

**6** **1,840mm lift**
Lifts into utes & most trucks, tips over fences.

**7** **Rupture resistant fuel tank**
Full vented cap with true-fill opening for easier refuelling.

FIELDQUIP ...a cut above the rest!

DINGO.COM.AU | FIELDQUIP.COM.AU

DINGO®